




# 818028

*X-TIGUA PRO 28LED 235W SIM DIF IP66*

Registry	
Net weight	9,5
Min order quantity	1
EAN Code	8014950138555
Gross Weight	10,5

Marks


Tec	
No. Led	
Lamp type	
Dimensions	
UGR index	
Hole type	
Output flux	
Treatment type	
Storage room temperature MIN	
Storage room temperature MAX	
Optics	
Flicker free	
Shock resistance	
Output efficiency	
Conductor section max	
Corrosion class	
CRI	CRI>=i
Life time	
Colour	
Tightening diameter	
Frequency	
Optics type	Anti

Protection degree	IP66
Diffuser type	Extraclear tempered glass, 4mm
Color temperature	4000 K
Power Supply Unit	Electronic
Color shift	C02
Luminous flux (TJ=25°C)	33250 lm
Min. Amb. Temp.	-30°C
Max. Amb. Temp.	+45°C
Nominal Operating Voltage	220V-240V
Manufacturing Material	Low coper aluminium alloy (EN 44300)
DC LED Driving current	700 mA
Mounting system	Adjustable bracket -110°+110°
Surface Finishing	Atoxic, anti UV polyester paint oven polymerized
Exposed surface	Lateral: 0,04 mq - Front: 0,18 mq
Power factor	>0,95
Outfit	power supply connector
Power on label (lighting)	MAX 235W
Photobiological risk	RG0 - Exempt Group
Control system/dimming	Standard on-off
Fixture power	235
Insulation Class	II